查询PBSS5320X供应商

DATA SHEET



PBSS5320X

20 V, 3 A
PNP low V_{CEsat} (BISS) transistor

Product specification
Supersedes data of 2003 Nov 27

2004 Nov 04

Philips
Semiconductors

PHILIPS

20 V, 3 A PNP low V_{CEsat} (BISS) transistor

PBSS5320X

FEATURES

- SOT89 (SC-62) package
- Low collector-emitter saturation voltage V_{CEsat}
- High collector current capability: I_C and I_{CM}
- Higher efficiency leading to less heat generation
- Reduced printed-circuit board requirements.

APPLICATIONS

- Power management
  - DC/DC converters
  - Supply line switching
  - Battery charger
  - LCD backlighting.
- Peripheral drivers
  - Driver in low supply voltage applications (e.g. lamps and LEDs)
  - Inductive load driver (e.g. relays, buzzers and motors).

DESCRIPTION

PNP low V_{CEsat} transistor in a SOT89 plastic package.
NPN complement: PBSS4320X.

MARKING

TYPE NUMBER	MARKING CODE
PBSS5320X	S45

QUICK REFERENCE DATA

SYMBOL	PARAMETER	MAX.	UNIT
V_{CEO}	collector-emitter voltage	–20	V
I_C	collector current (DC)	–3	A
I_{CM}	peak collector current	–5	A
R_{CEsat}	equivalent on-resistance	105	mΩ

PINNING

PIN	DESCRIPTION
1	emitter
2	collector
3	base



Fig.1 Simplified outline (SOT89) and symbol.

ORDERING INFORMATION

TYPE NUMBER	PACKAGE		
	NAME	DESCRIPTION	VERSION
PBSS5320X	SC-62	plastic surface mounted package; collector pad for good heat transfer; 3 leads	SOT89

LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 60134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
V_{CBO}	collector-base voltage	open emitter	–	–20	V
V_{CEO}	collector-emitter voltage	open base	–	–20	V
V_{EBO}	emitter-base voltage	open collector	–	–5	V
I_C	collector current (DC)	note 4	–	–3	A
I_{CM}	peak collector current	limited by $T_{j(max)}$	–	–5	A
I_B	base current (DC)		–	–0.5	A
P_{tot}	total power dissipation	$T_{amb} \leq 25$ °C			
		note 1	–	550	mW
		note 2	–	1	W
		note 3	–	1.4	W
		note 4	–	1.6	W
T_{stg}	storage temperature		–65	+150	°C
T_j	junction temperature		–	150	°C
T_{amb}	ambient temperature		–65	+150	°C

Notes

1. Device mounted on a FR4 printed-circuit board; single-sided copper; tin-plated; standard footprint.
2. Device mounted on a FR4 printed-circuit board; single-sided copper; tin-plated; mounting pad for collector 1 cm^2.
3. Device mounted on a FR4 printed-circuit board; single-sided copper; tin-plated; mounting pad for collector 6 cm^2.
4. Device mounted on a ceramic printed-circuit board 7 cm^2, single-sided copper, tin-plated.



(1) Ceramic PCB; 7 cm^2 mounting pad for collector.
(2) FR4 PCB; 6 cm^2 copper mounting pad for collector.
(3) FR4 PCB; 1 cm^2 copper mounting pad for collector.
(4) Standard footprint.

Fig.2 Power derating curves.

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
$R_{th(j-a)}$	thermal resistance from junction to ambient	in free air		
		note 1	225	K/W
		note 2	125	K/W
		note 3	90	K/W
		note 4	80	K/W
$R_{th(j-s)}$	thermal resistance from junction to soldering point		16	K/W

Notes

1. Device mounted on a FR4 printed-circuit board; single-sided copper; tin-plated; standard footprint.
2. Device mounted on a FR4 printed-circuit board; single-sided copper; tin-plated; mounting pad for collector 1 cm^2.
3. Device mounted on a FR4 printed-circuit board; single-sided copper; tin-plated; mounting pad for collector 6 cm^2.
4. Device mounted on a ceramic printed-circuit board 7 cm^2, single-sided copper, tin-plated.



Mounted on FR4 printed-circuit board; standard footprint.

(1) δ = 1. (3) δ = 0.5. (5) δ = 0.2. (7) δ = 0.05. (9) δ = 0.01.
(2) δ = 0.75. (4) δ = 0.33. (6) δ = 0.1. (8) δ = 0.02. (10) δ = 0.

Fig.3 Transient thermal impedance as a function of pulse time; typical values.



Mounted on FR4 printed-circuit board; mounting pad for collector 1 cm^2.

(1) δ = 1. (3) δ = 0.5. (5) δ = 0.2. (7) δ = 0.05. (9) δ = 0.01.
(2) δ = 0.75. (4) δ = 0.33. (6) δ = 0.1. (8) δ = 0.02. (10) δ = 0.

Fig.4 Transient thermal impedance as a function of pulse time; typical values.



Mounted on FR4 printed-circuit board; mounting pad for collector 6 cm^2.

(1) δ = 1. (3) δ = 0.5. (5) δ = 0.2. (7) δ = 0.05. (9) δ = 0.01.
(2) δ = 0.75. (4) δ = 0.33. (6) δ = 0.1. (8) δ = 0.02. (10) δ = 0.

Fig.5 Transient thermal impedance as a function of pulse time; typical values.

CHARACTERISTICS

T_{amb} = 25 °C unless otherwise specified.

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
I_{CBO}	collector-base cut-off current	V_{CB} = –20 V; I_E = 0 A	–	–	–100	nA
		V_{CB} = –20 V; I_E = 0 A; T_j = 150 °C	–	–	–50	μA
I_{CES}	collector-emitter cut-off current	V_{CE} = –20 V; V_{BE} = 0 V	–	–	–100	nA
I_{EBO}	emitter-base cut-off current	V_{EB} = –5 V; I_C = 0 A	–	–	–100	nA
h_{FE}	DC current gain	V_{CE} = –2 V				
		I_C = –0.1 A	220	–	–	
		I_C = –0.5 A	220	–	–	
		I_C = –1 A; note 1	200	–	–	
		I_C = –2 A; note 1	150	–	–	
		I_C = –3 A; note 1	100	–	–	
V_{CEsat}	collector-emitter saturation voltage	I_C = –0.5 A; I_B = –50 mA	–	–	–70	mV
		I_C = –1 A; I_B = –50 mA	–	–	–130	mV
		I_C = –2 A; I_B = –100 mA	–	–	–230	mV
		I_C = –3 A; I_B = –300 mA; note 1	–	–	–300	mV
R_{CEsat}	equivalent on-resistance	I_C = –3 A; I_B = –300 mA; note 1	–	90	105	mΩ
V_{BEsat}	base-emitter saturation voltage	I_C = –2 A; I_B = –100 mA	–	–1.1	–	V
		I_C = –3 A; I_B = –300 mA; note 1	–	–	–1.2	V
V_{BEon}	base-emitter turn-on voltage	V_{CE} = –2 V; I_C = –1 A	–1.1	–	–	V
f_T	transition frequency	I_C = –100 mA; V_{CE} = –5 V; f = 100 MHz	100	–	–	MHz
C_c	collector capacitance	V_{CB} = –10 V; I_E = i_e = 0 A; f = 1 MHz	–	–	50	pF

Note

1. Pulse test: $t_p \leq 300$ μs; $\delta \leq 0.02$.



V_{CE} = −2 V.
(1) T_{amb} = 100 °C.
(2) T_{amb} = 25 °C.
(3) T_{amb} = −55 °C.

Fig.6 DC current gain as a function of collector current; typical values.



V_{CE} = −2 V.
(1) T_{amb} = −55 °C.
(2) T_{amb} = 25 °C.
(3) T_{amb} = 100 °C.

Fig.7 Base-emitter voltage as a function of collector current; typical values.



I_C/I_B = 20.
(1) T_{amb} = 100 °C.
(2) T_{amb} = 25 °C.
(3) T_{amb} = −55 °C.

Fig.8 Collector-emitter saturation voltage as a function of collector current; typical values.



T_{amb} = 25 °C.
(1) I_C/I_B = 100.
(2) I_C/I_B = 50.
(3) I_C/I_B = 10.

Fig.9 Collector-emitter saturation voltage as a function of collector current; typical values.



I_C/I_B = 20.
(1) T_{amb} = –55 °C.
(2) T_{amb} = 25 °C.
(3) T_{amb} = 100 °C.

Fig.10 Base-emitter saturation voltage as a function of collector current; typical values.



T_{amb} = 25 °C.
(1) I_C/I_B = 100. (2) I_C/I_B = 50. (3) I_C/I_B = 10.

Fig.11 Equivalent on-resistance as a function of collector current; typical values.



I_C/I_B = 20.
(1) T_{amb} = 100 °C. (2) T_{amb} = 25 °C. (3) T_{amb} = –55 °C.

Fig.12 Equivalent on-resistance as a function of collector current; typical values.



T_{amb} = 25 °C.
(1) I_B = –25 mA. (5) I_B = –15 mA. (9) I_B = –5 mA.
(2) I_B = –22.5 mA. (6) I_B = –12.5 mA. (10) I_B = –2.5 mA.
(3) I_B = –20 mA. (7) I_B = –10 mA.
(4) I_B = –17.5 mA. (8) I_B = –7.5 mA.

Fig.13 Collector current as a function of collector-emitter voltage; typical values.

PACKAGE OUTLINE

Plastic surface mounted package; collector pad for good heat transfer; 3 leads **SOT89**



DIMENSIONS (mm are the original dimensions)

UNIT	A	b_{p1}	b_{p2}	b_{p3}	c	D	E	e	e_1	H_E	L_p	w
mm	1.6 1.4	0.48 0.35	0.53 0.40	1.8 1.4	0.44 0.23	4.6 4.4	2.6 2.4	3.0	1.5	4.25 3.75	1.2 0.8	0.13

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	JEITA			
SOT89		TO-243	SC-62			~~99-09-13~~ 04-08-03

DATA SHEET STATUS

LEVEL	DATA SHEET STATUS(1)	PRODUCT STATUS(2)(3)	DEFINITION
I	Objective data	Development	This data sheet contains data from the objective specification for product development. Philips Semiconductors reserves the right to change the specification in any manner without notice.
II	Preliminary data	Qualification	This data sheet contains data from the preliminary specification. Supplementary data will be published at a later date. Philips Semiconductors reserves the right to change the specification without notice, in order to improve the design and supply the best possible product.
III	Product data	Production	This data sheet contains data from the product specification. Philips Semiconductors reserves the right to make changes at any time in order to improve the design, manufacturing and supply. Relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN).

Notes

1. Please consult the most recently issued data sheet before initiating or completing a design.
2. The product status of the device(s) described in this data sheet may have changed since this data sheet was published. The latest information is available on the Internet at URL http://www.semiconductors.philips.com.
3. For data sheets describing multiple type numbers, the highest-level product status determines the data sheet status.

DEFINITIONS

Short-form specification — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

Limiting values definition — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 60134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

Application information — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors make no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

DISCLAIMERS

Life support applications — These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

Right to make changes — Philips Semiconductors reserves the right to make changes in the products - including circuits, standard cells, and/or software - described or contained herein in order to improve design and/or performance. When the product is in full production (status ‘Production’), relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN). Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no licence or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

Philips Semiconductors – a worldwide company

Contact information

For additional information please visit **http://www.semiconductors.philips.com**. Fax: **+31 40 27 24825**
For sales offices addresses send e-mail to: **sales.addresses@www.semiconductors.philips.com**.

© Koninklijke Philips Electronics N.V. 2004 SCA76

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Printed in The Netherlands R75/03/pp12 Date of release: 2004 Nov 04 Document order number: 9397 750 13887

Let's make things better.

Philips
Semiconductors

PHILIPS